SPECIFICATIONS

| General | AP515 | AP585 |
|---|---|---|
| Frequency Range | 400-470MHz;136-174MHz | |
| Channel Capacity | 32 | 128 |
| Zone Capacity | 2 | 8 |
| Channels Per Zone | 16 | |
| Channel Spacing | 12.5kHz/20kHz/25kHz | |
| Operating Voltage | 3.7V (rated) 7.4V (rated) | |
| Battery | 4000mAh 3.7V | 1500mAh 7.4V 2000mAh 7.4V (Optional) |
| Battery Life (5/5/90 Duty Cycle,High TX Power) | 18h | 12h(1500mAh) 16h(2000mAh) |
| Frequency Stability | ±0.5ppm | |
| Antenna Impedance | 50Ω | |
| Dimensions (H x W x D) | 105*55*29.5mm | 115*55*29.5mm |
| Weight(with antenna&battery) | 200g ±5g | 230g±5g |
| Display | \ | 1.44 inch LCD |
| BT (optional) | BT 5.0 BLE+EDR | |
| Receiver | | |
| Sensitivity | 0.18μV (12dB SINAD) | |
| Adjacent Channel Selectivity | TIA-603: 60dB@12.5kHz; 70dB@20/25kHz ETSI: 60dB@12.5kHz; 70dB@20/25kHz | |
| Intermodulation | TIA-603: 70dB@12.5/20/25kHz ETSI: 65dB@12.5/20/25kHz | |
| Spurious Response Rejection | TIA-603: 70dB@12.5/20/25kHz ETSI: 70dB@12.5/20/25kHz | |
| Blocking | TIA-603: 80dB; ETSI: 84dB | |
| Hum and Noise | 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz | |
| Rated Audio Power Output | 0.5W | 1W |
| Rated Audio Distortion | ≤3% | |
| Audio Response | +1~-3dB | |
| Conducted Spurious Emission | <-57dBm | |
| Transmitter | | |
| RF Power Output | VHF: 4-5W / 1W UHF: 3-4W / 1W | VHF: 5W / 1W UHF: 4W / 1W |
| FM Modulation | 11K0F3E@12.5kHz; 14K0F3E@20kHz; 16K0F3E@25kHz | |
| Conducted/Radiated Emission | -36dBm < 1GHz; -30dBm > 1GHz | |
| Modulation Limiting | ±2.5kHz@12.5kHz; ±4.0kHz@20kHz; ±5.0kHz@25kHz | |
| FM Hum&Noise | 40dB@12.5kHz; 43dB@20kHz; 45dB@25kHz | |
| Adjacent Channel Power | 60dB@12.5kHz; 70dB@20/25kHz | |
| Audio Response | +1 to -3dB | |
| Audio Distortion | ≤3% | |
| Environmental | | |
| Operating Temperature | 20001 | °C |
| | -20°C to +60°C | |
| Storage Temperature ESD | -40°C to +85°C IEC 61000-4-2 (Level 4) | |
| | ±8kV (contact); ±15kV (air) | |
| Dust and Water Intrusion | IEC60529-IP54 IEC60529-IP54 (IP67 optional) | |
| Humidity | MIL-STD-810 G | |
| Shock and Vibration | MIL-STD-810 G | |

ACCESSORIES

STANDARD ACCESSORIES:





















































0191 228 0466



www.apexradio.co.uk

11 Keel Row, The Watermark, Gateshead, NE11 9SZ

Hytera Communications Europe

www.facebook.com/

HyteraEurope

Hytera.Europe

939 Yeovil Road, Slough, Berkshire, SL1 4NH info@hytera-europe.com | www.hytera-europe.com





www.linkedin.com/company/hyteracommunications-uk



Subscribe on YouTube

Hytera reserves the right to modify the product design and the specifications. In case of a printing error, Hytera does not accept any liability. All specifications are subject to change without notice.













WORK SMARTLY AND EFFECTIVELY

Compact and light, yet the AP5 series is coupled with a package of features to make it easy to get your work done. Voice broadcast confirms the operation of a programmable button or changing the channel of non-display radios. Also there are three kinds of optional signaling to deliver critical information by a simple press.



TRUSTWORTHY QUALITY

Hytera has the world's largest professional communication production line, and manufactures each walkie-talkie in accordance with Industry 4.0 standards. Our strict supplier management system certification ensures each component meets the quality control requirements to ensure the consistency of product quality.

KEY FEATURES

- 32/128 channels
- Auto scan
- Vote scan
- Priority channel hunt
- Squelch
- Clear audio
- H/L power switching
- HDC1200 signaling/2-Tone signaling/
- 5-Tone signaling (optional)
- CTCSS/CDCSS
- Talk around
- Timeout timer
- Voice broadcast
- BT (optional)
- Type-C charge plug

